

Заказные аналого-цифровые микросхемы

Тип изделия	U_{CC} (V)	I_{CC} (mA)	T_{amb} °C	Корпус
Euro 1-5	4,5-5,5	0,01	-40 +85	PLCC84(84-pin plastic)
AS290-H	1,5-16,5	0,055	-65÷+85	H04.16-1B
ASXP193P	8-18	10	-45÷+85	2101.8-1(8-pin plastic DIP)
ASXP194P	8-18	6	-45÷+85	201.14-1(TO 116)
ASXP195P	8,5	0,2	-45÷+85	2101.8-1(8-pin plastic DIP)
ASXP642P	16	18	-45÷+85	2101.8-1(8-pin plastic DIP)
LMS 111	8,5	5	-45÷+85	238.18-1(18-pin plastic DIP)
VAC 330	8,5	3	-45÷+85	2101.18-1(18-pin plastic DIP)
CT 7073	14	3	-45÷+85	2101.16-1(16-pin plastic DIP)
AS194H	35	20	-60 +125	3101.8-1(TO-99)
LC360	8,5	1,0	-45 +85	2101.8-1(8-pin plastic DIP)
MT420	5 - 15	5	-45 +85	SOIC 24(24-pin plastic)
LCD1041	8,5	0,2	-45÷+85	SOIC 32